

CHOOSE THE RIGHT ROGUE.

STICK/TIG WELDERS.

	ROGUE ES 130i	ROGUE ES 180i	ROGUE ET 200iP Pro
Rated Output	<p>STICK 25% @ 130 A / 25.2 V (230 V Output) 60% @ 84 A / 23.4 V (230 V Output) 100% @ 65 A / 22.6 V (230 V Output)</p> <p>25% @ 90 A / 23.6 V (120 V Output) 60% @ 58 A / 22.3 V (120 V Output) 100% @ 45 A / 21.8 V (120 V Output)</p> <p>TIG 25% @ 130 A / 15.2 V (230 V Output) 60% @ 84 A / 13.4 V (230 V Output) 100% @ 65 A / 12.6 V (230 V Output)</p> <p>25% @ 130 A / 15.2 V (120 V Output) 60% @ 84 A / 13.4 V (120 V Output) 100% @ 65 A / 12.6 V (120 V Output)</p>	<p>STICK 25% @ 180 A / 27.2 V (230 V Output) 60% @ 116 A / 24.6 V (230 V Output) 100% @ 90 A / 23.6 V (230 V Output)</p> <p>25% @ 110 A / 24.4 V (120 V Output) 60% @ 70 A / 22.8 V (120 V Output) 100% @ 55 A / 22.2 V (120 V Output)</p> <p>TIG 25% @ 180 A / 17.2 V (230 V Output) 60% @ 116 A / 14.6 V (230 V Output) 100% @ 90 A / 13.6 V (230 V Output)</p> <p>25% @ 140 A / 15.6 V (120 V Output) 60% @ 90 A / 13.6 V (120 V Output) 100% @ 70 A / 12.8 V (120 V Output)</p>	<p>STICK 25% @ 200 A / 28.0 V (230 V Output) 60% @ 129 A / 25.2 V (230 V Output) 100% @ 100 A / 24.0 V (230 V Output)</p> <p>25% @ 110 A / 24.4 V (120 V Output) 60% @ 70 A / 22.8 V (120 V Output) 100% @ 55 A / 22.2 V (120 V Output)</p> <p>TIG 25% @ 200 A / 18.0 V (230 V Output) 60% @ 129 A / 15.2 V (230 V Output) 100% @ 100 A / 14.0 V (230 V Output)</p> <p>25% @ 140 A / 15.6 V (120 V Output) 60% @ 90 A / 13.6 V (120 V Output) 100% @ 70 A / 12.8 V (120 V Output)</p>
Max Output	130 A	180 A	200 A
Input Rating	120 V / 230 V VAC ±15% (50/60 Hz)	120 V / 230 V VAC ±15% (50/60 Hz)	120 V / 230 V VAC ±15% (50/60 Hz)
OCV	78 V DC	78 V DC	78 V DC
Max Plate Thickness	1/4"	3/8"	3/8"
Weight	18.2 lb. (8.25 kg)	18.2 lb. (8.25 kg)	21.2 lb. (9.62 kg)
Welding Processes	STICK / LIVE TIG	STICK / LIVE TIG	STICK / HF TIG / LIFT TIG

From SMAW to TIG, and now with MIG welding capabilities, the entire Rogue lineup was designed for welders who dare to be different.

MIG WELDERS.

	ROGUE EM 125 MIG	ROGUE EM 140 MIG	ROGUE EM 190 MIG
Rated Output	MIG 30% @ 90 A	MIG 30% @ 90 A	MIG 30% @ 145 A
Max Output	125 A	140 A	190 A
Input Voltage	120 V	120 V	230 V
OCV	50 V	50 V	78 V
Max Plate Thickness	3/16"	1/4"	3/8"
Weight	27.7 lb. (12.56 kg)	28.8 lb. (13.06 kg)	37.3 lb. (16.92 kg)
Display	14-Segment LED, 2x3	14-Segment LED, 2x3	5" TFT
Premium Accessories	Integrated MIG Gun	Tweco Fusion 180 MIG Gun Victor Regulator / Flow Gauge	Tweco Fusion 180 MIG Gun Victor Regulator / Flow Gauge
Welding Processes	MIG (GMAW) Flux Cored (FCAW)	MIG (GMAW) Flux Cored (FCAW)	MIG (GMAW) Flux Cored (FCAW)